
# 40-6502 & 40-6512 Manual-Leveling

# **Rotary Laser Level**

Emits a vertical<sup>-</sup> laser beam with simultaneous 90° split beam



Scan line can be moved clockwise or counterclockwise

# Emits a horizontal laser beam

## FEATURES:

- Emits a horizontal laser beam
- Emits a vertical laser beam with simultaneous 90° split beam
- Large and small scan modes achieve a chalk line
- Scan line can be moved clockwise or counter-clockwise
- Variable rotation speed 150-300RPM
- Rugged co-molded housing

#### 40-6502 INCLUDES:

- Manual-leveling rotary laser level
- 4 "AA" alkaline batteries
- Tinted glasses
- Instruction manual with warranty card
- Soft-sided carrying case

#### 40-6512 INCLUDES:

- Manual-leveling rotary laser level
- 4 "AA" alkaline batteries
- Wall/ceiling mount
- 8' grade rod
- Detector with 2 "AAA" batteries and clamp
- Tinted glasses
- Magnetic target
- Elevating tripod
- Instruction manual with warranty card
- Hard-shell carrying case

|      | (- | 12    |              |   |
|------|----|-------|--------------|---|
|      |    |       | -            |   |
| 0000 | -  | -ACCI | PRO IDUNSON- | - |



| UPC<br>049448 | Sugg List<br>Price |  |
|---------------|--------------------|--|
|               |                    |  |
| 065028        | \$250.00           |  |
| 065127        | \$638.00           |  |
|               | 065028             |  |

# **Rotary Laser Level**

# **APPLICATIONS:**

# **Construction Contractors**

- Leveling
- Checking cut and fill
- Setting foundations & footings
- Concrete pours
- Septic tanks and basement excavations
- Acoustical ceiling & drywall

#### **Builders**

- Align & plumb walls
- Metal stud and wood framers

### **Deck Builders**

- Level deck floors
- Establish diagonals & footings

#### Farmers


Contour farming, drainage

#### Landscapers

Terracing & retaining walls













# SPECIFICATIONS:

| Laser wavelength     | 635nm <u>+</u> 10nm                                 |
|----------------------|---|
| Laser classification | Class IIIa  |
| Maximum power output | <u>&lt;</u> 5mw                                     |
| Accuracy             | <u>+</u> 1/4"/100'                                  |
| Interior range       | Up to 200' diameter depending upon light conditions |
| Exterior range       | Up to 800' diameter with detector                   |
| Power supply         | 4 "AA" alkaline batteries (included)                |
| Battery life         | Approx. battery life 15 hours continuous use        |
| Dimensions           | 5.118" x 5.118" x 6.141"                            |
| Weight               | 1.653 lbs   |
| Working temperature  | 14°F to 113°F                                       |
| Center screw thread  | 5/8"-11   |
| Rotation speeds      | 150-300 RPM   |
| Scanning Modes       | Big, Small, DOT                                     |
| IP protection class  | 54  |



For additional information on Johnson® products, please call our Customer Service Department at 800.563.8553 © 2009 Johnson Level & Tool Mfg. Co, Inc. Mequon, WI 53092